
WebTest Documentation

Release 3.0.0.dev0

Ian Bicking

Dec 17, 2020

Contents

1	Status & License	3
2	Installation	5
3	What This Does	7
4	Quick start	9
5	Contents	11
5.1	Functional Testing of Web Applications	11
5.2	webtest API	19
5.3	Contribute to webtest project	30
5.4	News	32
6	License	43
	Python Module Index	45
	Index	47

author Ian Bicking <ianb@colorstudy.com>

maintainer Gael Pasgrimaud <gael@gawel.org>

CHAPTER 1

Status & License

WebTest is an extraction of `paste.fixture.TestApp`, rewriting portions to use [WebOb](#). It is under active development as part of the Pylons cloud of packages.

Feedback and discussion should take place on the [Pylons discuss list](#), and bugs should go into the [Github tracker](#).

This library is licensed under an *MIT-style license*.

CHAPTER 2

Installation

You can use `pip` or `easy_install` to get the latest stable release:

```
$ pip install WebTest
$ easy_install WebTest
```

Or if you want the development version:

```
$ pip install https://nodeload.github.com/Pylons/webtest/tar.gz/master
```

What This Does

WebTest helps you test your WSGI-based web applications. This can be any application that has a WSGI interface, including an application written in a framework that supports WSGI (which includes most actively developed Python web frameworks – almost anything that even nominally supports WSGI should be testable).

With this you can test your web applications without starting an HTTP server, and without poking into the web framework shortcutting pieces of your application that need to be tested. The tests WebTest runs are entirely equivalent to how a WSGI HTTP server would call an application. By testing the full stack of your application, the WebTest testing model is sometimes called a *functional test*, *integration test*, or *acceptance test* (though the latter two are not particularly good descriptions). This is in contrast to a *unit test* which tests a particular piece of functionality in your application. While complex programming tasks are often suited to unit tests, template logic and simple web programming is often best done with functional tests; and regardless of the presence of unit tests, no testing strategy is complete without high-level tests to ensure the entire programming system works together.

WebTest helps you create tests by providing a convenient interface to run WSGI applications and verify the output.

CHAPTER 4

Quick start

The most important object in WebTest is *TestApp*, the wrapper for WSGI applications. It also allows you to perform HTTP requests on it. To use it, you simply instantiate it with your WSGI application.

Note: If your WSGI application requires any configuration, you must set that up manually in your tests.

Here is a basic application:

```
>>> def application(environ, start_response):
...     headers = [('Content-Type', 'text/html; charset=utf8'),
...                ('Content-Length', str(len(body)))]
...     start_response('200 OK', headers)
...     return [body]
```

Wrap it into a *TestApp*:

```
>>> from webtest import TestApp
>>> app = TestApp(application)
```

Then you can get the response of a HTTP GET:

```
>>> resp = app.get('/')
```

And check the results, like response's status:

```
>>> assert resp.status == '200 OK'
>>> assert resp.status_int == 200
```

Response's headers:

```
>>> assert resp.content_type == 'text/html'
>>> assert resp.content_length > 0
```

Or response's body:

```
>>> resp.mustcontain('<html>')
>>> assert 'form' in resp
```

WebTest can do much more. In particular, it can handle *Form handling*.

5.1 Functional Testing of Web Applications

5.1.1 TestApp

Making Requests

To make a request, use:

```
app.get('/path', [params], [headers], [extra_environ], ...)
```

This call to `get()` does a request for `/path`, with any params, extra headers or WSGI environment keys that you indicate. This returns a `TestResponse` object, based on `webob.response.Response`. It has some additional methods to make it easier to test.

If you want to do a POST request, use:

```
app.post('/path', {'vars': 'values'}, [headers], [extra_environ],
          [upload_files], ...)
```

Specifically the second argument of `post()` is the *body* of the request. You can pass in a dictionary (or dictionary-like object), or a string body (dictionary objects are turned into HTML form submissions).

You can also pass in the keyword argument `upload_files`, which is a list of `[(fieldname, filename, field_content)]`. File uploads use a different form submission data type to pass the structured data.

You can use `put()` and `delete()` for PUT and DELETE requests.

Making JSON Requests

Webtest provide some facilities to test json apis.

The `*_json` methods will transform data to json before POST/PUT and add the correct `Content-Type` for you.

Also Response have an attribute `json` to allow you to retrieve json contents as a python dict.

Doing *POST* request with `webtest.app.TestApp.post_json()`:

```
>>> resp = app.post_json('/resource/', dict(id=1, value='value'))
>>> print(resp.request)
POST /resource/ HTTP/1.0
Content-Length: 27
Content-Type: application/json
...

>>> resp.json == {'id': 1, 'value': 'value'}
True
```

Doing *GET* request with `webtest.app.TestApp.get()` and using `json`:

To just parse body of the response, use `Response.json`:

```
>>> resp = app.get('/resource/1/')
>>> print(resp.request)
GET /resource/1/ HTTP/1.0
...

>>> resp.json == {'id': 1, 'value': 'value'}
True
```

Modifying the Environment & Simulating Authentication

The best way to simulate authentication is if your application looks in `environ['REMOTE_USER']` to see if someone is authenticated. Then you can simply set that value, like:

```
app.get('/secret', extra_environ=dict(REMOTE_USER='bob'))
```

If you want *all* your requests to have this key, do:

```
app = TestApp(my_app, extra_environ=dict(REMOTE_USER='bob'))
```

If you have to use HTTP authorization you can use the `.authorization` property to set the `HTTP_AUTHORIZATION` key of the `extra_environ` dictionary:

```
app = TestApp(my_app)
app.authorization = ('Basic', ('user', 'password'))
```

You can also use bearer token or JWT authorization types:

```
app = TestApp(my_app)
app.authorization = ('Bearer', 'mytoken')
# or
app.authorization = ('JWT', 'myjwt')
```

Testing a non wsgi application

You can use WebTest to test an application on a real web server. Just pass an url to the `TestApp` instead of a WSGI application:


```
app = TestApp('http://my.cool.websi.te')
```

You can also use the `WEBTEST_TARGET_URL` env var to switch from a WSGI application to a real server without having to modify your code:

```
os.environ['WEBTEST_TARGET_URL'] = 'http://my.cool.websi.te'
app = TestApp(wsgiapp) # will use the WEBTEST_TARGET_URL instead of the wsgiapp
```

By default the proxy will use `httplib` but you can use other backends by adding an anchor to your url:

```
app = TestApp('http://my.cool.websi.te#urllib3')
app = TestApp('http://my.cool.websi.te#requests')
app = TestApp('http://my.cool.websi.te#restkit')
```

What Is Tested By Default

A key concept behind WebTest is that there's lots of things you shouldn't have to check everytime you do a request. It is assumed that the response will either be a 2xx or 3xx response; if it isn't an exception will be raised (you can override this for a request, of course). The WSGI application is tested for WSGI compliance with a slightly modified version of `wsgiref.validate` (modified to support arguments to `InputWrapper.readline`) automatically. Also it checks that nothing is printed to the `environ['wsgi.errors']` error stream, which typically indicates a problem (one that would be non-fatal in a production situation, but if you are testing is something you should avoid).

To indicate another status is expected, use the keyword argument `status=404` to (for example) check that it is a 404 status, or `status="*"` to allow any status, or `status="400 Custom Bad Request"` to use custom reason phrase.

If you expect errors to be printed, use `expect_errors=True`.

5.1.2 TestResponse

The response object is based on `webob.response.Response` with some additions to help with testing.

The inherited attributes that are most interesting:

- response.status:** The text status of the response, e.g., "200 OK".
- response.status_int:** The text status_int of the response, e.g., 200.
- response.headers:** A dictionary-like object of the headers in the response.
- response.body:** The text body of the response.
- response.text:** The unicode text body of the response.
- response.normal_body:** The whitespace-normalized¹ body of the response.
- response.request:** The `webob.request.BaseRequest` object used to generate this response.

The added methods:

- response.follow(**kw):** Follows the redirect, returning the new response. It is an error if this response wasn't a redirect. All keyword arguments are passed to `webtest.app.TestApp` (e.g., `status`). Returns another response object.
- response.maybe_follow(**kw):** Follows all redirects; does nothing if this response is not a redirect. All keyword arguments are passed to `webtest.app.TestApp` (e.g., `status`). Returns another response object.

¹ The whitespace normalization replace sequences of whitespace characters and `\n \r \t` by a single space.

x in response: Returns True if the string is found in the response body. Whitespace is normalized for this test.

response.mustcontain(string1, string2, no=string3): Raises an error if any of the strings are not found in the response. If a string of a string list is given as *no* keyword argument, raise an error if one of those are found in the response. It also prints out the response in that case, so you can see the real response.

response.showbrowser(): Opens the HTML response in a browser; useful for debugging.

str(response): Gives a slightly-compacted version of the response. This is compacted to remove newlines, making it easier to use with `doctest`.

response.click(description=None, linkid=None, href=None, anchor=None, index=None, verbose=False): Clicks the described link (see `click()`)

response.forms: Return a dictionary of forms; you can use both indexes (refer to the forms in order) or the string ids of forms (if you've given them ids) to identify the form. See [Form handling](#) for more on the form objects.

response.form: If there is just a single form, this returns that. It is an error if you use this and there are multiple forms.

Form handling

Getting a form

If you have a single html form in your page, just use the `.form` attribute:

```
>>> res = app.get('/form.html')
>>> form = res.form
```

You can use the form index if your html contains more than one form:

```
>>> form = res.forms[0]
```

Or the form id:

```
>>> form = res.forms['myform']
```

You can check form attributes:

```
>>> print(form.id)
myform
>>> print(form.action)
/form-submit
>>> print(form.method)
POST
```

Filling a form

You can fill out and submit forms from your tests. Fields are a dict like object:

```
>>> # dict of fields
>>> form.fields.items()
[(u'text', [<Text name="text">]), ..., (u'submit', [<Submit name="submit">])]
```

You can check the current value:

```
>>> print(form['text'].value)
Foo
```

Then you fill it in fields:

```
>>> form['text'] = 'Bar'
>>> # When names don't point to a single field:
>>> form.set('text', 'Bar', index=0)
```

Field types

Input and textarea fields

```
>>> print(form['textarea'].value)
Some text
>>> form['textarea'] = 'Some other text'
```

You can force the value of an hidden field:

```
>>> form['hidden'].force_value('2')
```

Select fields

Simple select:

```
>>> print(form['select'].value)
option2
>>> form['select'] = 'option1'
```

Select multiple:

```
>>> print(form['multiple'].value)
['option2', 'option3']
>>> form['multiple'] = ['option1']
```

You can select an option by its text with `.select()`:

```
>>> form['select'].select(text="Option 2")
>>> print(form['select'].value)
option2
```

For select multiple use `.select_multiple()`:

```
>>> form['multiple'].select_multiple(texts=["Option 1", "Option 2"])
>>> print(form['multiple'].value)
['option1', 'option2']
```

Select fields can only be set to valid values (i.e., values in an `<option>`) but you can also use `.force_value()` to enter values not present in an option.

```
>>> form['select'].force_value(['optionX'])
>>> form['multiple'].force_value(['optionX'])
```

Checkbox

You can check if the checkbox is checked and its value:

```
>>> print(form['checkbox'].checked)
False
>>> print(form['checkbox'].value)
None
```

You can change the status with the value:

```
>>> form['checkbox'] = True
```

Or with the checked attribute:

```
>>> form['checkbox'].checked = True
```

If the checkbox is checked then you'll get the value:

```
>>> print(form['checkbox'].checked)
True
>>> print(form['checkbox'].value)
checkbox 1
```

If the checkbox has no value then it will be 'on' if you checked it:

```
>>> print(form['checkbox2'].value)
None
>>> form['checkbox2'].checked = True
>>> print(form['checkbox2'].value)
on
```

If there are multiple checkboxes of the same name, you can assign a list to that name to check all the checkboxes whose value is present in the list:

```
>>> form['checkboxes'] = ['a', 'c']
>>> print(form.get('checkboxes', index=0).value)
a
>>> print(form.get('checkboxes', index=1).value)
None
>>> print(form.get('checkboxes', index=2).value)
c
```

Radio

```
>>> print(form['radio'].value)
Radio 2
>>> form['radio'] = 'Radio 1'
```

File

You can deal with file upload by using the Upload class:

```
>>> from webtest import Upload
>>> form['file'] = Upload('README.rst')
>>> form['file'] = Upload('README.rst', b'data')
>>> form['file'] = Upload('README.rst', b'data', 'text/x-rst')
```

Submit a form

Then you can submit the form:

```
>>> # Submit with no particular submit button pressed:
>>> res = form.submit()
>>> # Or submit a button:
>>> res = form.submit('submit')
>>> print(res)
Response: 200 OK
Content-Type: text/plain
text=Bar
...
submit=Submit
```

You can also select a specific submit button by its index:

```
>>> res = form.submit('submit', index=1)
>>> print(res)
Response: 200 OK
Content-Type: text/plain
...
submit=Submit 2
```

And you can select it by its value:

```
>>> res = form.submit('submit', value="Submit 2")
>>> print(res)
Response: 200 OK
Content-Type: text/plain
...
submit=Submit 2
```

Parsing the Body

There are several ways to get parsed versions of the response. These are the attributes:

response.html: Return a `BeautifulSoup` version of the response body:

```
>>> res = app.get('/index.html')
>>> res.html
<html><body><div id="content">hey!</div></body></html>
>>> res.html.__class__
<class '...BeautifulSoup'>
```

response.xml: Return an `ElementTree` version of the response body:

```
>>> res = app.get('/document.xml')
>>> res.xml
```

(continues on next page)

(continued from previous page)

```

<Element 'xml' ...>
>>> res.xml[0].tag
'message'
>>> res.xml[0].text
'hey!'

```

response.lxml: Return an `lxml` version of the response body:

```

>>> res = app.get('/index.html')
>>> res.lxml
<Element html at ...>
>>> res.lxml.xpath('//body/div')[0].text
'hey!'

>>> res = app.get('/document.xml')
>>> res.lxml
<Element xml at ...>
>>> res.lxml[0].tag
'message'
>>> res.lxml[0].text
'hey!'

```

response.pyquery: Return a `PyQuery` version of the response body:

```

>>> res.pyquery('message')
[<message>]
>>> res.pyquery('message').text()
'hey!'

```

response.json: Return the parsed JSON (parsed with `simplejson`):

```

>>> res = app.get('/object.json')
>>> sorted(res.json.values())
[1, 2]

```

In each case the content-type must be correct or an `AttributeError` is raised. If you do not have the necessary library installed (none of them are required by `WebTest`), you will get an `ImportError`.

5.1.3 WSGI Debug application

`webtest.debugapp.debug_app` is a faker WSGI app to help to test `webtest`.

Examples of use :

```

>>> import webtest
>>> from webtest.debugapp import debug_app
>>> app = webtest.TestApp(debug_app)
>>> res = app.post('/', params='foobar')
>>> print(res.body)
CONTENT_LENGTH: 6
CONTENT_TYPE: application/x-www-form-urlencoded
HTTP_HOST: localhost:80
...
wsgi.url_scheme: 'http'
wsgi.version: (1, 0)

```

(continues on next page)

(continued from previous page)

```
-- Body -----
foobar
```

Here, you can see, `foobar` in `body` when you pass `foobar` in `app.post` `params` argument.

You can also define the status of response :

```
>>> res = app.post('/?status=302', params='foobar')
>>> print(res.status)
302 Found
```

5.1.4 Framework Hooks

Frameworks can detect that they are in a testing environment by the presence (and truth) of the WSGI environmental variable `"paste.testing"` (the key name is inherited from `paste.fixture`).

More generally, frameworks can detect that something (possibly a test fixture) is ready to catch unexpected errors by the presence and truth of `"paste.throw_errors"` (this is sometimes set outside of testing fixtures too, when an error-handling middleware is in place).

Frameworks that want to expose the inner structure of the request may use `"paste.testing_variables"`. This will be a dictionary – any values put into that dictionary will become attributes of the response object. So if you do `env["paste.testing_variables"]['template'] = template_name` in your framework, then `response.template` will be `template_name`.

5.2 webtest API

Routines for testing WSGI applications.

5.2.1 webtest.app.TestApp

class `webtest.app.TestApp` (*app*, *extra_environ=None*, *relative_to=None*, *use_unicode=True*, *cookiejar=None*, *parser_features=None*, *json_encoder=None*, *lint=True*)
Wraps a WSGI application in a more convenient interface for testing. It uses extended version of `webob.BaseRequest` and `webob.Response`.

Parameters

- **app** (*WSGI application*) – May be an WSGI application or Paste Deploy app, like `'config:filename.ini#test'`.

New in version 2.0.

It can also be an actual full URL to an http server and `webtest` will proxy requests with `WSGIProxy2`.

- **extra_environ** (*dict*) – A dictionary of values that should go into the environment for each request. These can provide a communication channel with the application.
- **relative_to** (*string*) – A directory used for file uploads are calculated relative to this. Also `config:` URIs that aren't absolute.
- **cookiejar** (*CookieJar instance*) – `cookielib.CookieJar` alike API that keeps cookies across requests.

cookies

A convenient shortcut for a dict of all cookies in `cookiejar`.

Parameters

- **parser_features** (*string or list*) – Passed to BeautifulSoup when parsing responses.
- **json_encoder** (*A subclass of json.JSONEncoder*) – Passed to `json.dumps` when encoding json
- **lint** (*A boolean*) – If True (default) then check that the application is WSGI compliant

RequestClass

alias of `TestRequest`

authorization

Allow to set the HTTP_AUTHORIZATION environ key. Value should look like one of the following:

- ('Basic', ('user', 'password'))
- ('Bearer', 'mytoken')
- ('JWT', 'myjwt')

If value is None the the HTTP_AUTHORIZATION is removed

delete (*url, params="", headers=None, extra_environ=None, status=None, expect_errors=False, content_type=None, xhr=False*)

Do a DELETE request. Similar to `get()`.

Returns `webtest.TestResponse` instance.

delete_json (*url, params=<NoDefault>, **kw*)

Do a DELETE request. Very like the `delete` method.

`params` are dumped to json and put in the body of the request. Content-Type is set to `application/json`.

Returns a `webtest.TestResponse` object.

do_request (*req, status=None, expect_errors=None*)

Executes the given webob Request (`req`), with the expected `status`. Generally `get()` and `post()` are used instead.

To use this:

```
req = webtest.TestRequest.blank('url', ...args...)
resp = app.do_request(req)
```

Note: You can pass any keyword arguments to `TestRequest.blank()`, which will be set on the request. These can be arguments like `content_type`, `accept`, etc.

encode_multipart (*params, files*)

Encodes a set of parameters (typically a name/value list) and a set of files (a list of (name, filename, file_body, mimetype)) into a typical POST body, returning the (`content_type`, `body`).

get (*url, params=None, headers=None, extra_environ=None, status=None, expect_errors=False, xhr=False*)

Do a GET request given the url path.

Parameters

- **params** – A query string, or a dictionary that will be encoded into a query string. You may also include a URL query string on the `url`.
- **headers** (*dictionary*) – Extra headers to send.
- **extra_envIRON** (*dictionary*) – Environmental variables that should be added to the request.
- **status** (*integer or string*) – The HTTP status code you expect in response (if not 200 or 3xx). You can also use a wildcard, like '3*' or '*'.
- **expect_errors** (*boolean*) – If this is False, then if anything is written to `environ` `wsgi.errors` it will be an error. If it is True, then non-200/3xx responses are also okay.
- **xhr** (*boolean*) – If this is true, then marks response as ajax. The same as `headers={'X-Requested-With': 'XMLHttpRequest', }`

Returns `webtest.TestResponse` instance.

get_authorization()

Allow to set the HTTP_AUTHORIZATION environ key. Value should look like one of the following:

- ('Basic', ('user', 'password'))
- ('Bearer', 'mytoken')
- ('JWT', 'myjwt')

If value is None the the HTTP_AUTHORIZATION is removed

head(*url, params=None, headers=None, extra_envIRON=None, status=None, expect_errors=False, xhr=False*)

Do a HEAD request. Similar to `get()`.

Returns `webtest.TestResponse` instance.

options(*url, headers=None, extra_envIRON=None, status=None, expect_errors=False, xhr=False*)

Do a OPTIONS request. Similar to `get()`.

Returns `webtest.TestResponse` instance.

patch(*url, params="", headers=None, extra_envIRON=None, status=None, upload_files=None, expect_errors=False, content_type=None, xhr=False*)

Do a PATCH request. Similar to `post()`.

Returns `webtest.TestResponse` instance.

patch_json(*url, params=<NoDefault>, **kw*)

Do a PATCH request. Very like the `patch` method.

`params` are dumped to json and put in the body of the request. Content-Type is set to `application/json`.

Returns a `webtest.TestResponse` object.

post(*url, params="", headers=None, extra_envIRON=None, status=None, upload_files=None, expect_errors=False, content_type=None, xhr=False*)

Do a POST request. Similar to `get()`.

Parameters

- **params** – Are put in the body of the request. If `params` is an iterator, it will be urlencoded. If it is a string, it will not be encoded, but placed in the body directly.

Can be a `collections.OrderedDict` with `webtest.forms.Upload` fields included:

```
app.post('/myurl', collections.OrderedDict([
    ('textfield1', 'value1'),
    ('uploadfield', webapp.Upload('filename.txt', 'contents'),
    ('textfield2', 'value2'])))
```

- **upload_files** (*list*) – It should be a list of (fieldname, filename, file_content). You can also use just (fieldname, filename) and the file contents will be read from disk.
- **content_type** (*string*) – HTTP content type, for example *application/json*.
- **xhr** (*boolean*) – If this is true, then marks response as ajax. The same as headers={'X-REQUESTED-WITH': 'XMLHttpRequest', }

Returns `webtest.TestResponse` instance.

post_json (*url*, *params*=<NoDefault>, ***kw*)

Do a POST request. Very like the `post` method.

params are dumped to json and put in the body of the request. Content-Type is set to `application/json`.

Returns a `webtest.TestResponse` object.

put (*url*, *params*=", *headers*=None, *extra_environ*=None, *status*=None, *upload_files*=None, *expect_errors*=False, *content_type*=None, *xhr*=False)

Do a PUT request. Similar to `post()`.

Returns `webtest.TestResponse` instance.

put_json (*url*, *params*=<NoDefault>, ***kw*)

Do a PUT request. Very like the `put` method.

params are dumped to json and put in the body of the request. Content-Type is set to `application/json`.

Returns a `webtest.TestResponse` object.

request (*url_or_req*, *status*=None, *expect_errors*=False, ***req_params*)

Creates and executes a request. You may either pass in an instantiated `TestRequest` object, or you may pass in a URL and keyword arguments to be passed to `TestRequest.blank()`.

You can use this to run a request without the intermediary functioning of `TestApp.get()` etc. For instance, to test a WebDAV method:

```
resp = app.request('/new-col', method='MKCOL')
```

Note that the request won't have a body unless you specify it, like:

```
resp = app.request('/test.txt', method='PUT', body='test')
```

You can use `webtest.TestRequest`:

```
req = webtest.TestRequest.blank('/url/', method='GET')
resp = app.do_request(req)
```

reset ()

Resets the state of the application; currently just clears saved cookies.

set_cookie (*name*, *value*)

Sets a cookie to be passed through with requests.

set_parser_features (*parser_features*)

Changes the parser used by BeautifulSoup. See its documentation to know the supported parsers.

5.2.2 webtest.app.TestRequest

class webtest.app.**TestRequest** (*environ*, *charset=None*, *unicode_errors=None*, *decode_param_names=None*, ***kw*)

Bases: `webob.request.BaseRequest`

A subclass of `webob.Request`

ResponseClass

alias of `webtest.response.TestResponse`

5.2.3 webtest.response.TestResponse

class webtest.response.**TestResponse** (*body=None*, *status=None*, *headerlist=None*, *app_iter=None*, *content_type=None*, *conditional_response=None*, *charset=<object object>*, ***kw*)

Bases: `webob.response.Response`

Instances of this class are returned by `TestApp` methods.

click (*description=None*, *linkid=None*, *href=None*, *index=None*, *verbose=False*, *extra_environ=None*)

Click the link as described. Each of `description`, `linkid`, and `url` are *patterns*, meaning that they are either strings (regular expressions), compiled regular expressions (objects with a `search` method), or callables returning true or false.

All the given patterns are ANDed together:

- `description` is a pattern that matches the contents of the anchor (HTML and all – everything between `<a...>` and ``)
- `linkid` is a pattern that matches the `id` attribute of the anchor. It will receive the empty string if no `id` is given.
- `href` is a pattern that matches the `href` of the anchor; the literal content of that attribute, not the fully qualified attribute.

If more than one link matches, then the `index` link is followed. If `index` is not given and more than one link matches, or if no link matches, then `IndexError` will be raised.

If you give `verbose` then messages will be printed about each link, and why it does or doesn't match. If you use `app.click(verbose=True)` you'll see a list of all the links.

You can use multiple criteria to essentially assert multiple aspects about the link, e.g., where the link's destination is.

clickbutton (*description=None*, *buttonid=None*, *href=None*, *index=None*, *verbose=False*)

Like `click()`, except looks for link-like buttons. This kind of button should look like `<button onclick="...location.href='url'...">`.

follow (***kw*)

If this response is a redirect, follow that redirect. It is an error if it is not a redirect response. Any keyword arguments are passed to `webtest.app.TestApp.get`. Returns another `TestResponse` object.

form

If there is only one form on the page, return it as a *Form* object; raise a `TypeError` if there are no form or multiple forms.

forms

Returns a dictionary containing all the forms in the pages as *Form* objects. Indexes are both in order (from zero) and by form id (if the form is given an id).

See *Form handling* for more info on form objects.

goto (*href, method='get', **args*)

Go to the (potentially relative) link *href*, using the given method ('get' or 'post') and any extra arguments you want to pass to the `webtest.app.TestApp.get()` or `webtest.app.TestApp.post()` methods.

All hostnames and schemes will be ignored.

html

Returns the response as a *BeautifulSoup* object.

Only works with HTML responses; other content-types raise `AttributeError`.

json

Return the response as a JSON response. The content type must be one of json type to use this.

lxml

Returns the response as an *lxml* object. You must have *lxml* installed to use this.

If this is an HTML response and you have *lxml* 2.x installed, then an `lxml.html.HTML` object will be returned; if you have an earlier version of *lxml* then a `lxml.HTML` object will be returned.

maybe_follow (***kw*)

Follow all redirects. If this response is not a redirect, do nothing. Any keyword arguments are passed to `webtest.app.TestApp.get`. Returns another *TestResponse* object.

mustcontain (**strings, no=[]*)

Assert that the response contains all of the strings passed in as arguments.

Equivalent to:

```
assert string in res
```

Can take a *no* keyword argument that can be a string or a list of strings which must not be present in the response.

normal_body

Return the whitespace-normalized body

pyquery

Returns the response as a *PyQuery* object.

Only works with HTML and XML responses; other content-types raise `AttributeError`.

showbrowser ()

Show this response in a browser window (for debugging purposes, when it's hard to read the HTML).

unicode_normal_body

Return the whitespace-normalized body, as unicode

xml

Returns the response as an *ElementTree* object.

Only works with XML responses; other content-types raise `AttributeError`

5.2.4 webtest.forms

Helpers to fill and submit forms.

```
class webtest.forms.Checkbox (*args, **attrs)
    Bases: webtest.forms.Field
    Field representing <input type="checkbox">

    checked
        Returns True if checkbox is checked.

    force_value (value)
        Like setting a value, except forces it (even for, say, hidden fields).
```

```
class webtest.forms.Email (form, tag, name, pos, value=None, id=None, **attrs)
    Bases: webtest.forms.Field
    Field representing <input type="email">

    force_value (value)
        Like setting a value, except forces it (even for, say, hidden fields).
```

```
class webtest.forms.Field (form, tag, name, pos, value=None, id=None, **attrs)
    Bases: object
    Base class for all Field objects.

    classes
        Dictionary of field types (select, radio, etc)

    value
        Set/get value of the field.

    force_value (value)
        Like setting a value, except forces it (even for, say, hidden fields).
```

```
class webtest.forms.File (form, tag, name, pos, value=None, id=None, **attrs)
    Bases: webtest.forms.Field
    Field representing <input type="file">

    force_value (value)
        Like setting a value, except forces it (even for, say, hidden fields).
```

```
class webtest.forms.Form (response, text, parser_features='html.parser')
    Bases: object
    This object represents a form that has been found in a page.

    Parameters
        • response – webob.response.TestResponse instance
        • text – Unparsed html of the form

    text
        the full HTML of the form.

    action
        the relative URI of the action.

    method
        the HTTP method (e.g., 'GET').
```

id

the id, or None if not given.

enctype

encoding of the form submission

fields

a dictionary of fields, each value is a list of fields by that name. `<input type="radio">` and `<select>` are both represented as single fields with multiple options.

field_order

Ordered list of field names as found in the html.

FieldClass

alias of `Field`

get (*name*, *index=None*, *default=<NoDefault>*)

Get the named/indexed field object, or *default* if no field is found. Throws an `AssertionError` if no field is found and no *default* was given.

lint ()

Check that the html is valid:

- each field must have an id
- each field must have a label

select (*name*, *value=None*, *text=None*, *index=None*)

Like `.set()`, except also confirms the target is a `<select>` and allows selecting options by text.

select_multiple (*name*, *value=None*, *texts=None*, *index=None*)

Like `.set()`, except also confirms the target is a `<select multiple>` and allows selecting options by text.

set (*name*, *value*, *index=None*)

Set the given name, using *index* to disambiguate.

submit (*name=None*, *index=None*, *value=None*, ***args*)

Submits the form. If *name* is given, then also select that button (using *index* or *value* to disambiguate)“.

Any extra keyword arguments are passed to the `webtest.TestResponse.get()` or `webtest.TestResponse.post()` method.

Returns a `webtest.TestResponse` object.

submit_fields (*name=None*, *index=None*, *submit_value=None*)

Return a list of [(*name*, *value*), ...] for the current state of the form.

Parameters

- **name** – Same as for `submit()`
- **index** – Same as for `submit()`

upload_fields ()

Return a list of file field tuples of the form:

```
(field name, file name)
```

or:

```
(field name, file name, file contents).
```

class `webtest.forms.Hidden` (*form, tag, name, pos, value=None, id=None, **attrs*)

Bases: `webtest.forms.Text`

Field representing `<input type="hidden">`

force_value (*value*)

Like setting a value, except forces it (even for, say, hidden fields).

class `webtest.forms.MultipleSelect` (**args, **attrs*)

Bases: `webtest.forms.Field`

Field representing `<select multiple="multiple">`

force_value (*values*)

Like setting a value, except forces it (even for, say, hidden fields).

class `webtest.forms.Radio` (**args, **attrs*)

Bases: `webtest.forms.Select`

Field representing `<input type="radio">`

force_value (*value*)

Like setting a value, except forces it (even for, say, hidden fields).

class `webtest.forms.Select` (**args, **attrs*)

Bases: `webtest.forms.Field`

Field representing `<select />` form element.

force_value (*value*)

Like setting a value, except forces it (even for, say, hidden fields).

class `webtest.forms.Submit` (*form, tag, name, pos, value=None, id=None, **attrs*)

Bases: `webtest.forms.Field`

Field representing `<input type="submit">` and `<button>`

force_value (*value*)

Like setting a value, except forces it (even for, say, hidden fields).

class `webtest.forms.Text` (*form, tag, name, pos, value=None, id=None, **attrs*)

Bases: `webtest.forms.Field`

Field representing `<input type="text">`

force_value (*value*)

Like setting a value, except forces it (even for, say, hidden fields).

class `webtest.forms.Textarea` (*form, tag, name, pos, value=None, id=None, **attrs*)

Bases: `webtest.forms.Text`

Field representing `<textarea>`

force_value (*value*)

Like setting a value, except forces it (even for, say, hidden fields).

class `webtest.forms.Upload` (*filename, content=None, content_type=None*)

Bases: `object`

A file to upload:

```
>>> Upload('filename.txt', 'data', 'application/octet-stream')
<Upload "filename.txt">
>>> Upload('filename.txt', 'data')
<Upload "filename.txt">
```

(continues on next page)

(continued from previous page)

```
>>> Upload("README.txt")
<Upload "README.txt">
```

Parameters

- **filename** – Name of the file to upload.
- **content** – Contents of the file.
- **content_type** – MIME type of the file.

5.2.5 webtest.http

This module contains some helpers to deal with the real http world.

class `webtest.http.StoppableWSGIServer` (*application, *args, **kwargs*)

Bases: `waitress.server.TcpWSGIServer`

`StoppableWSGIServer` is a `TcpWSGIServer` which run in a separated thread. This allow to use tools like `casperjs` or `selenium`.

Server instance have an `application_url` attribute formated with the server host and port.

classmethod `create` (*application, **kwargs*)

Start a server to serve `application`. Return a server instance.

run ()

Run the server

shutdown ()

Shutdown the server

wait (*retries=30*)

Wait until the server is started

wrapper (*environ, start_response*)

Wrap the wsgi application to override some path:

`/__application__`: allow to ping the server.

`/__file__?__file__={path}`: serve the file found at path

`webtest.http.check_server` (*host, port, path_info='/', timeout=3, retries=30*)

Perform a request until the server reply

5.2.6 webtest.lint

Middleware to check for obedience to the WSGI specification.

Some of the things this checks:

- Signature of the application and `start_response` (including that keyword arguments are not used).
- Environment checks:
 - Environment is a dictionary (and not a subclass).
 - That all the required keys are in the environment: `REQUEST_METHOD`, `SERVER_NAME`, `SERVER_PORT`, `wsgi.version`, `wsgi.input`, `wsgi.errors`, `wsgi.multithread`, `wsgi.multiprocess`, `wsgi.run_once`

- That HTTP_CONTENT_TYPE and HTTP_CONTENT_LENGTH are not in the environment (these headers should appear as CONTENT_LENGTH and CONTENT_TYPE).
- Warns if QUERY_STRING is missing, as the cgi module acts unpredictably in that case.
- That CGI-style variables (that don't contain a .) have (non-unicode) string values
- That wsgi.version is a tuple
- That wsgi.url_scheme is 'http' or 'https' (@@: is this too restrictive?)
- Warns if the REQUEST_METHOD is not known (@@: probably too restrictive).
- That SCRIPT_NAME and PATH_INFO are empty or start with /
- That at least one of SCRIPT_NAME or PATH_INFO are set.
- That CONTENT_LENGTH is a positive integer.
- That SCRIPT_NAME is not '/' (it should be '', and PATH_INFO should be '/').
- That wsgi.input has the methods read, readline, readlines, and __iter__
- That wsgi.errors has the methods flush, write, writelines
- The status is a string, contains a space, starts with an integer, and that integer is in range (> 100).
- That the headers is a list (not a subclass, not another kind of sequence).
- That the items of the headers are tuples of 'native' strings (i.e. bytestrings in Python2, and unicode strings in Python3).
- That there is no 'status' header (that is used in CGI, but not in WSGI).
- That the headers don't contain newlines or colons, end in _ or -, or contain characters codes below 037.
- That Content-Type is given if there is content (CGI often has a default content type, but WSGI does not).
- That no Content-Type is given when there is no content (@@: is this too restrictive?)
- That the exc_info argument to start_response is a tuple or None.
- That all calls to the writer are with strings, and no other methods on the writer are accessed.
- That wsgi.input is used properly:
 - .read() is called with zero or one argument
 - That it returns a string
 - That readline, readlines, and __iter__ return strings
 - That .close() is not called
 - No other methods are provided
- That wsgi.errors is used properly:
 - .write() and .writelines() is called with a string, except with python3
 - That .close() is not called, and no other methods are provided.
- The response iterator:
 - That it is not a string (it should be a list of a single string; a string will work, but perform horribly).
 - That .next() returns a string
 - That the iterator is not iterated over until start_response has been called (that can signal either a server or application error).

- That `.close()` is called (doesn't raise exception, only prints to `sys.stderr`, because we only know it isn't called when the object is garbage collected).

`webtest.lint.middleware(application, global_conf=None)`

When applied between a WSGI server and a WSGI application, this middleware will check for WSGI compliance on a number of levels. This middleware does not modify the request or response in any way, but will throw an `AssertionError` if anything seems off (except for a failure to close the application iterator, which will be printed to `stderr` – there's no way to throw an exception at that point).

5.2.7 `webtest.debugapp`

class `webtest.debugapp.DebugApp` (*form=None, show_form=False*)
 Bases: `object`

The WSGI application used for testing

`webtest.debugapp.make_debug_app(global_conf, **local_conf)`

An application that displays the request environment, and does nothing else (useful for debugging and test purposes).

5.3 Contribute to webtest project

5.3.1 Getting started

Get your working copy :

```
$ git clone https://github.com/Pylons/webtest.git
$ cd webtest
$ virtualenv .
$ . bin/activate
$ python setup.py dev
```

Now, you can hack.

5.3.2 Execute tests

```
$ bin/pytest
Doctest: forms.rst ... ok
Doctest: index.rst ... ok

...

test_url_class (tests.test_testing.TestTesting) ... ok
tests.test_testing.test_print_unicode ... °C
ok

Name                               Stmts  Miss  Cover   Missing
-----
webtest                             18      0  100%
webtest.app                         603     92   85%  48, 61-62, 94, 98, 212-221, 264-265, 268-272,
↪ 347, 379-386, 422, 426-428, 432-434, 455, 463, 471, 473, 488, 496-497, 515, 520-
↪ 527, 548, 553-554, 558-559, 577, 592, 597-598, 618, 624, 661-664, 742, 808, 872,
↪ 940-941, 945-948, 961-964, 975, 982, 995, 1000, 1006, 1010, 1049, 1051, 1095-1096,
↪ 1118-1119, 1122-1127, 1135-1136, 1148, 1155-1160, 1175
```

(continues on next page)

(continued from previous page)

```

webtest.compat          50      11      78%   28-34, 55-56, 61-62
webtest.debugapp       58       0     100%
webtest.ext            80       0     100%
webtest.forms         324      23      93%   23, 49, 58, 61, 92, 116, 177, 205, 411, 478, ↵
↪482-486, 491-493, 522, 538, 558-561
webtest.http           78       0     100%
webtest.lint          215      45      79%   135, 176, 214-216, 219-224, 227-231, 234, ↵
↪243-244, 247, 250-251, 254, 263-264, 270, 274, 307, 311, 335, 359, 407, 424-427, ↵
↪441-444, 476-479, 493, 508
webtest.sel            479     318     34%   38-39, 45-46, 64-78, 88-108, 120, 126, 151-
↪153, 156-158, 164-165, 168-191, 194-201, 219-231, 236, 240, 243-259, 263-297, 301-
↪306, 316-326, 331-336, 340, 344, 347-352, 357-359, 364, 392-394, 397-404, 408, 412-
↪417, 421, 425-426, 430, 434, 438, 442, 445, 448-457, 470-480, 483-485, 488, 492, ↵
↪495, 503, 506, 515-516, 520, 524, 528, 533, 538, 542-544, 547, 560-565, 576, 579, ↵
↪582, 593-596, 599-602, 605-606, 617-620, 623-642, 668-677, 680-688, 715, 720, 732, ↵
↪735, 744-754, 757-762, 770-779, 791, 794, 805-809, 813-826, 838-842
webtest.utils          99      11      89%   19-20, 23, 26, 32, 38, 100, 109, 152-154
-----
TOTAL                   2004     500     75%
-----
Ran 70 tests in 14.940s

```

5.3.3 Use tox to test many Python versions

Tox installation :

```
$ pip install tox
$ tox
```

Launch tests with *tox* :

```
$ bin/tox
py26: commands succeeded
py27: commands succeeded
py32: commands succeeded
py33: commands succeeded
```

To execute test on all python versions, you need to have `python2.6`, `python2.7`, `python3.2` and `python3.3` in your `PATH`.

5.3.4 Generate documentation

```
$ pip install Sphinx
$ cd docs
$ make html
../bin/sphinx-build -b html -d _build/doctrees  _build/html
Running Sphinx v1.1.3
loading pickled environment... done
...
build succeeded, 3 warnings.

Build finished. The HTML pages are in _build/html.
```

5.3.5 Tips

You can use *WSGI Debug application* object to test *webtest*.

5.4 News

5.4.1 3.0.0 (unreleased)

- Dropped support for Python 2.7 and 3.5.
- Added support for Python 3.9.
- Clean up dependencies and requirements.
- Switch from Travis to GitHub Actions for building and testing.

5.4.2 2.0.35 (2020-04-27)

- python3.8 compat
- Remove use of deprecated splittype and splithost

5.4.3 2.0.34 (2020-01-29)

- Fix the test `length == 0` in `check_content_type`.
- Treat `<input type="search">` like `<input type="text">`.
- Handle query parameters for the head method.

5.4.4 2.0.33 (2019-02-09)

- Fixed #210. Allow to reset select multiple with `field.value = []`
- Support for `PYTHONOPTIMIZE=2`, fix tests on `PYTHONOPTIMIZE=1, 2`
- Fixed #196. Fix deprecation warnings for `collections` to use `collections.abc` for `Iterable` on Python 3.

5.4.5 2.0.32 (2018-10-05)

- remove invalid email from `setup.py`

5.4.6 2.0.31 (2018-10-05)

- py33 is no longer supported. It may works but has been removed from tox config
- Fixed #205: Use empty string as default value for submit and button
- tests use `pytest`
- docs use the standard Pylons template on RTD

5.4.7 2.0.30 (2018-06-23)

- Add `Email` class for input fields with type "email".
- Documentation bearer token and JWT authorization

5.4.8 2.0.29 (2017-10-21)

- Bugfix: Preserve submit order for radio inputs.
- Fixed #186: avoid `UnicodeDecodeError` in linter with py2 when a header contain non ascii chars

5.4.9 2.0.28 (2017-08-01)

- Fixed #185: Fix strict cookie policy
- Fixed #146: Improve fields value checking when enctype is multipart
- Fixed #119: Assertion error should be raised when you have non-string response header
- Bugfix: Allow to set an int value to form fields when enctype is multipart
- Added py36 to tox.ini / .travis.yaml

5.4.10 2.0.27 (2017-03-15)

- Bugfix: Allow to use `set_cookie` when `HTTP_HOST` is set
- Fix #177: `resp.json` now always decode body as utf8

5.4.11 2.0.26 (2017-03-05)

- Added JWT auth support
- Always show response body when response status is invalid

5.4.12 2.0.25 (2017-02-05)

- Fix #173: Do not omit file uploads without a file from post. [Michael Howitz]

5.4.13 2.0.24 (2016-12-16)

- Drop python 2.6 support. Newer versions may still work if you use waitress < 1.0
- Remove bs4 warnings
- Docs improvements
- Tests are WebOb 1.7.x compatible

5.4.14 2.0.23 (2016-07-21)

- Create universal wheels.

5.4.15 2.0.22 (2016-07-21)

- Fix #160: Do not guess encoding if response's charset is set.

5.4.16 2.0.21 (2016-04-12)

- PR #154 Allow Bearer auth
- PR #147,#148 Take care of REFERER when using form.submit(), .click() and .clickbutton()
- PR #145 Allow to override content-type when using json methods

5.4.17 2.0.20 (2015-11-03)

- nothing new release. just try to make wheel available on pypi

5.4.18 2.0.19 (2015-11-01)

- fixed #131 prevent passing HTML parameters that conflict with Field kwargs
- fixed #135 Document that WSGIProxy2 is required for "using webtest with a real url"
- fixed #136 reset values of select multiple
- drop py32 support (still work but test dependencies fail)

5.4.19 2.0.18 (2015-02-05)

- Avoid deprecation warning with py3.4

5.4.20 2.0.17 (2014-12-20)

- Properly check for default cookiejar arguments [Julian Berman]
- Avoid raising encoding errors from debugapp (needed to use with WSGIProxy2) [Laurence Rowe]

5.4.21 2.0.16 (2014-09-19)

- Fixed #110. Forced values for Radio inputs are no longer ignored by value property on get. [bayprogrammer]
- Added method TestApp.set_parser_features to change the parser_features used by BeautifulSoup. [tomas-moreyra]
- Added app.set_cookie [luhn]

5.4.22 2.0.15 (2014-04-17)

- Fixed #73. Python < 2.6.5 does not support unicode as keyword arguments names. [Stepan Kolesnik]
- Fixed #84 Application cookies for localhost are no longer ignored [gawel]

- Fixed #89 remove WSGIWarning: You are not supposed to send a body in a DELETE request because we now have a good reason for that. See <https://stackoverflow.com/questions/299628/is-an-entity-body-allowed-for-an-http-delete-request/299701#299701> [gawel]
- Fixed #92 You can now override TestApp.JSONEncoder to use a custom encoder [gawel]
- Fixed #93 Support basic authentication [gawel]
- Fixed #103 Broken "Edit me on GitHub" links in documentation [gawel]
- Fixed #106 Make wrapping the app in the lint middleware optional [dmlayton]
- Fixed #107 Explicit error message when WSGIProxy2 is not installer [gawel]
- Fixed #108 `cgi.parse_qs` is pending deprecation [gawel]

5.4.23 2.0.14 (2014-01-23)

- Allow `.select()` on `<select>`s and `<select multiple>`s. [Markus Bertheau]

5.4.24 2.0.13 (2014-01-23)

- Allow selecting `<select>` options by text [Markus Bertheau]

5.4.25 2.0.12 (2014-01-17)

- Ignore the `value` attribute of file inputs [Markus Bertheau]
- Allow selecting the form submit button by its value [Markus Bertheau]

5.4.26 2.0.11 (2013-12-29)

- Depend on `unittest2` only for Python versions lower than 2.7 [iElectric]
- Add an optional parameter to `TestApp`, allowing the user to specify the parser used by BeautifulSoup [lyndsysimon]

5.4.27 2.0.10 (2013-11-14)

- Make `StoppableWSGIServer` thread daemon [Irowe]

5.4.28 2.0.9 (2013-09-18)

- Make sure `Upload.content_type` is not ignored <https://github.com/Pylons/webtest/pull/88> [Marius Gedminas]

5.4.29 2.0.8 (2013-09-17)

- Allow checking/unchecking a set of same-named checkboxes by assigning a list of values. [carljm]
- fix "AttributeError: 'InputWrapper' object has no attribute 'seek'" [iElectric]
- Added `xhr=True` parameter to `TestApp.get`, `TestApp.post`, `TestApp.head`, `TestApp.delete` [kharandziuk]

- Remove old (and broken?) casperjs/selenium backward compat imports. Fix <https://github.com/gawel/webtest-selenium/issues/9> [gawel]
- Allow optionally specifying the MIME type of an uploaded form file. Fixes #86 [Marius Gedminas]

5.4.30 2.0.7 (2013-08-07)

- Detect JSON if mimetype ends with +json, such as application/vnd.webtest+json [homm]
- Fixed #72. Use WSGIServer new api even if there waitress has backward compat. [gawel]
- Fixed #50. Corrected default value for the delete params argument. [noonat]
- Be sure to decode the content if it is gzipped before returning it [Alexis Métaireau]

5.4.31 2.0.6 (2013-05-23)

- fixed #64. cookiejar api has changed in python3.3 [gawel]
- allow to use a fixed StopableWSGIServer [gawel]
- Do not alter the BeautifulSoup object when parsing forms. [Georges Dubus]
- Remove first newline while parse textarea block, how modern browsers does. [Victor Safronovich] pull #69

5.4.32 2.0.5 (2013-04-12)

- Ignore select.error (not socket.error) following StopableWSGIServer.shutdown. [Laurence Rowe]
- Handle the short form of <select multiple> [Marius Gedminas]

5.4.33 2.0.4 (2013-03-28)

- Correctly handle <option> elements with no value attribute [Marius Gedminas]
- Ignore socket.error following StopableWSGIServer.shutdown. [Laurence Rowe]
- <button> without type='submit' attribute is treated as Submit control [Andrey Lebedev].
- Support for redirects having relative "Location" header [Andrey Lebedev]

5.4.34 2.0.3 (2013-03-19)

- Treat strings in the WSGI environment as native strings, compliant with PEP-3333. [wosc]

5.4.35 2.0.2 (2013-03-15)

- Allow TestResponse.click() to match HTML content again. [ender672]
- Support secure cookies [Andrey Lebedev]

5.4.36 2.0.1 (2013-03-05)

- Added Password field [diarmuidbourke]
- re-allow to use unknown field type. Like `type="email"`. [gawel]
- Don't let BeautifulSoup use lxml. Fix GH-51 [kmike]
- added `webtest.response.TestResponse.maybe_follow()` method [kmike]

5.4.37 2.0 (2013-02-25)

- drop `zc.buildout` usage for development, now using only `virtualenv` [Domen Kožar]
- Backward incompatibility : Removed the `anchor` argument of `webtest.response.TestResponse.click()` and the `button` argument of `webtest.response.TestResponse.clickbutton()`. It is for the greater good. [madjar]
- Rewrote API documentation [Domen Kožar]
- Added `wsgiproxy` support to do HTTP request to an URL [gawel]
- Use BeautifulSoup4 to parse forms [gawel]
- Added `webtest.app.TestApp.patch_json` [gawel]
- Implement `webtest.app.TestApp.cookiejar` support and kind of keep `webtest.app.TestApp.cookies` functionality. `webtest.app.TestApp.cookies` should be treated as read-only. [Domen Kožar]
- Split Selenium integration into separate package `webtest-selenium` [gawel]
- Split casperjs integration into separate package `webtest-casperjs` [gawel]
- Test coverage improvements [harobed, cdevienne, arthru, Domen Kožar, gawel]
- Fully implement decoding of HTML entities
- Fix tox configuration

5.4.38 1.4.2

- fix tests error due to CLRF in a tarball

5.4.39 1.4.1

- add travis-ci
- migrate repository to <https://github.com/Pylons/webtest>
- Fix a typo in `apps.py`: `selectedIndicies`
- Preserve field order during parsing (support for `deform` and such)
- allow equals sign in the cookie by splitting name-value-string pairs on the first '=' sign as per <https://tools.ietf.org/html/rfc6265#section-5.2>
- fix an error when you use `AssertionError(response)` with unicode chars in response

5.4.40 1.4.0

- added `webtest.ext` - allow to use `casperjs`

5.4.41 1.3.6

- fix #42 Check uppercase method.
- fix #36 Radio can use forced value.
- fix #24 Include test fixtures.
- fix bug when trying to print a response which contain some unicode chars

5.4.42 1.3.5

- fix #39 Add PATCH to acceptable methods.

5.4.43 1.3.4

- fix #33 Remove `CaptureStdout`. Do nothing and break `pdb`
- use `OrderedDict` to store fields in form. See #31
- fix #38 Allow to post falsey values.
- fix #37 Allow `Content-Length: 0` without `Content-Type`
- fix #30 bad link to `pyquery` documentation
- Never catch `NameError` during iteration

5.4.44 1.3.3

- added `post_json`, `put_json`, `delete_json`
- fix #25 `params` dictionary of `webtest.AppTest.post()` does not support unicode values

5.4.45 1.3.2

- improve `showbrowser`. fixed #23
- `print_stderr` fail with unicode string on `python2`

5.4.46 1.3.1

- Added `.option()` #20
- Fix #21
- Full `python3` compat

5.4.47 1.3

- Moved TestApp to app.py
- Added selenium testing framework. See `sel` module.

5.4.48 1.2.4

- Accept lists for `app.post(url, params=[...])`
- Allow to use url that starts with the `SCRIPT_NAME` found in `extra_environ`
- Fix #16 Default content-type is now correctly set to `application/octet-stream`
- Fix #14 and #18 Allow to use `.delete(params={})`
- Fix #12

5.4.49 1.2.3

- Fix #10, now `TestApp.extra_environ` doesn't take precedence over a WSGI environment passed in through the request.
- Removed stray print

5.4.50 1.2.2

- Revert change to cookies that would add " around cookie values.
- Added property `webtest.Response.pyquery()` which returns a `PyQuery` object.
- Set `base_url` on `resp.lxml`
- Include tests and docs in tarball.
- Fix sending in `webob.Request` (or `webtest.TestRequest`) objects.
- Fix handling forms with file uploads, when no file is selected.
- Added `extra_environ` argument to `webtest.TestResponse.click()`.
- Fixed/added wildcard statuses, like `status="4*"`
- Fix file upload fields in forms: allow upload field to be empty.
- Added support for single-quoted html attributes.
- `TestResponse` now has unicode support. It is turned on by default for all responses with charset information. **This is backward incompatible change** if you rely (e.g. in doctests) on parsed form fields or responses returned by `json` and `lxml` methods being encoded strings when charset header is in response. In order to switch to old behaviour pass `use_unicode=False` flag to `TestApp` constructor.

5.4.51 1.2.1

- Added method `TestApp.request()`, which can be used for sending requests with different methods (e.g., MKCOL). This method sends all its keyword arguments to `webtest.TestRequest.blank()` and then executes the request. The parameters are somewhat different than other methods (like `webtest.TestApp.get()`), as they match WebOb's attribute names exactly (the other methods were written before WebOb existed).

- Removed the copying of stdout to stderr during requests.
- Fix file upload fields in forms (#340) – you could upload files with `webtest.TestApp.post()`, but if you use `resp.form` file upload fields would not work (from rcs-comp.com and Matthew Desmarais).

5.4.52 1.2

- Fix form inputs; text inputs always default to the empty string, and unselected radio inputs default to nothing at all. From Daniele Paoella.
- Fix following links with fragments (these fragments should not be sent to the WSGI application). From desmaj.
- Added `force_value` to select fields, like `res.form['select'].force_value("new_value")`. This makes it possible to simulate forms that are dynamically updated. From Matthew Desmarais.
- Fixed `webtest.Response.mustcontain()` when you pass in a `no=[strings]` argument.

5.4.53 1.1

- Changed the `__str__` of responses to make them more doctest friendly:
 - All headers are displayed capitalized, like Content-Type
 - Headers are sorted alphabetically
- Changed `__repr__` to only show the body length if the complete body is not shown (for short bodies the complete body is in the repr)
- Note: **these are backward incompatible changes** if you are using doctest (you'll have to update your doctests with the new format).
- Fixed exception in the `.delete` method.
- Added a `content_type` argument to `app.post` and `app.put`, which sets the Content-Type of the request. This is more convenient when testing REST APIs.
- Skip links in `<script>...</script>` tags (since that's not real markup).

5.4.54 1.0.2

- Don't submit unnamed form fields.
- Checkboxes with no explicit value send on (previously they sent checked, which isn't what browsers send).
- Support for `<select multiple>` fields (from Matthew Desmarais)

1.0.1 —

- Fix the `TestApp` validator's `InputWrapper` lacking support for `readline` with an argument as needed by the `cgi` module.

5.4.55 1.0

- Keep URLs in-tact in cases such as `app.get('http://www.python.org')` (so `HTTP_HOST=www.python.org`, etc).
- Fix `lxml.html` import, so `lxml 2.0` users can get HTML `lxml` objects from `resp.lxml`
- Treat `<input type="image">` like a submit button.

- Use `BaseCookie` instead of `SimpleCookie` for storing cookies (avoids quoting cookie values).
- Accept any `params` argument that has an `items` method (like `MultiDict`)

5.4.56 0.9

Initial release

Copyright (c) 2010 Ian Bicking and Contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

W

`webtest`, [19](#)
`webtest.debugapp`, [30](#)
`webtest.forms`, [25](#)
`webtest.http`, [28](#)
`webtest.lint`, [28](#)

A

action (*webtest.forms.Form* attribute), 25
authorization (*webtest.app.TestApp* attribute), 20

C

check_server() (in module *webtest.http*), 28
Checkbox (class in *webtest.forms*), 25
checked (*webtest.forms.Checkbox* attribute), 25
classes (*webtest.forms.Field* attribute), 25
click() (*webtest.response.TestResponse* method), 23
clickbutton() (*webtest.response.TestResponse* method), 23
cookies (*webtest.app.TestApp* attribute), 19
create() (*webtest.http.StopableWSGIServer* class method), 28

D

DebugApp (class in *webtest.debugapp*), 30
delete() (*webtest.app.TestApp* method), 20
delete_json() (*webtest.app.TestApp* method), 20
do_request() (*webtest.app.TestApp* method), 20

E

Email (class in *webtest.forms*), 25
encode_multipart() (*webtest.app.TestApp* method), 20
enctype (*webtest.forms.Form* attribute), 26

F

Field (class in *webtest.forms*), 25
field_order (*webtest.forms.Form* attribute), 26
FieldClass (*webtest.forms.Form* attribute), 26
fields (*webtest.forms.Form* attribute), 26
File (class in *webtest.forms*), 25
follow() (*webtest.response.TestResponse* method), 23
force_value() (*webtest.forms.Checkbox* method), 25
force_value() (*webtest.forms.Email* method), 25
force_value() (*webtest.forms.Field* method), 25
force_value() (*webtest.forms.File* method), 25

force_value() (*webtest.forms.Hidden* method), 27
force_value() (*webtest.forms.MultipleSelect* method), 27
force_value() (*webtest.forms.Radio* method), 27
force_value() (*webtest.forms.Select* method), 27
force_value() (*webtest.forms.Submit* method), 27
force_value() (*webtest.forms.Text* method), 27
force_value() (*webtest.forms.Textarea* method), 27
Form (class in *webtest.forms*), 25
form (*webtest.response.TestResponse* attribute), 23
forms (*webtest.response.TestResponse* attribute), 24

G

get() (*webtest.app.TestApp* method), 20
get() (*webtest.forms.Form* method), 26
get_authorization() (*webtest.app.TestApp* method), 21
goto() (*webtest.response.TestResponse* method), 24

H

head() (*webtest.app.TestApp* method), 21
Hidden (class in *webtest.forms*), 26
html (*webtest.response.TestResponse* attribute), 24

I

id (*webtest.forms.Form* attribute), 25

J

json (*webtest.response.TestResponse* attribute), 24

L

lint() (*webtest.forms.Form* method), 26
lxml (*webtest.response.TestResponse* attribute), 24

M

make_debug_app() (in module *webtest.debugapp*), 30
maybe_follow() (*webtest.response.TestResponse* method), 24

method (*webtest.forms.Form* attribute), 25
middleware() (in module *webtest.lint*), 30
MultipleSelect (class in *webtest.forms*), 27
mustcontain() (*webtest.response.TestResponse* method), 24

N

normal_body (*webtest.response.TestResponse* attribute), 24

O

options() (*webtest.app.TestApp* method), 21

P

patch() (*webtest.app.TestApp* method), 21
patch_json() (*webtest.app.TestApp* method), 21
post() (*webtest.app.TestApp* method), 21
post_json() (*webtest.app.TestApp* method), 22
put() (*webtest.app.TestApp* method), 22
put_json() (*webtest.app.TestApp* method), 22
pyquery (*webtest.response.TestResponse* attribute), 24

R

Radio (class in *webtest.forms*), 27
request() (*webtest.app.TestApp* method), 22
RequestClass (*webtest.app.TestApp* attribute), 20
reset() (*webtest.app.TestApp* method), 22
ResponseClass (*webtest.app.TestRequest* attribute), 23
run() (*webtest.http.StopableWSGIServer* method), 28

S

Select (class in *webtest.forms*), 27
select() (*webtest.forms.Form* method), 26
select_multiple() (*webtest.forms.Form* method), 26
set() (*webtest.forms.Form* method), 26
set_cookie() (*webtest.app.TestApp* method), 22
set_parser_features() (*webtest.app.TestApp* method), 22
showbrowser() (*webtest.response.TestResponse* method), 24
shutdown() (*webtest.http.StopableWSGIServer* method), 28
StopableWSGIServer (class in *webtest.http*), 28
Submit (class in *webtest.forms*), 27
submit() (*webtest.forms.Form* method), 26
submit_fields() (*webtest.forms.Form* method), 26

T

TestApp (class in *webtest.app*), 19
TestRequest (class in *webtest.app*), 23
TestResponse (class in *webtest.response*), 23

Text (class in *webtest.forms*), 27
text (*webtest.forms.Form* attribute), 25
Textarea (class in *webtest.forms*), 27

U

unicode_normal_body (*webtest.response.TestResponse* attribute), 24
Upload (class in *webtest.forms*), 27
upload_fields() (*webtest.forms.Form* method), 26

V

value (*webtest.forms.Field* attribute), 25

W

wait() (*webtest.http.StopableWSGIServer* method), 28
webtest (module), 19
webtest.debugapp (module), 30
webtest.forms (module), 25
webtest.http (module), 28
webtest.lint (module), 28
wrapper() (*webtest.http.StopableWSGIServer* method), 28

X

xml (*webtest.response.TestResponse* attribute), 24